

HOT SPOT<sup>®</sup> COLLECTION

# PACE<sup>™</sup>



5

People

24

Jets

Double  
Lounge

Seating

115 or 230

Voltage

6'10" x 6'10" x 33"

Dimensions

FROG<sup>®</sup> In-Line Cartridge Ready

Water Care

HOT SPOT® COLLECTION

# PACE™




Pace spa shown with Alpine White shell, Havana cabinet and Havana Hot Spot Collection Step.


**Shell Colors**



**Cabinet Colors**



**Cover Colors**



<b>Seating Capacity</b>	5 people	<b>Control System</b>	IQ 2020® 115 V / 20 amp,** 60 Hz (Includes G.F.C.I. protected power cord) or 115 V / 30 amp*** or 220 V / 50 amp,*** 60 Hz
<b>Dimensions</b>	6'10" x 6'10" x 33" / 2.08 m x 2.08 m x 0.84 m	<b>Lighting – Interior</b>	10 multi-color LED points of light, dimmable
<b>Water Capacity</b>	300 gallons / 1,135 liters	<b>Lighting – Exterior</b>	4 multi-color LED points of light, dimmable
<b>Weight</b>	775 lbs. / 350 kg dry; 4,150 lbs. / 1,880 kg filled*	<b>Heater</b>	No-Fault® 1,000 W / 115 V or 4,000 W / 230 V
<b>Jets</b>	24 total • 3 XL Directional Hydromassage jets • 2 Directional Hydromassage jets • 2 Rotary Hydromassage jets • 17 Directional Precision® jets	<b>Energy Efficiency</b>	FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
<b>SmartJet™ System</b>	Included	<b>Effective Filtration Area</b>	30 sq. ft., top loading
<b>Water Feature</b>	Included	<b>Vinyl Cover</b>	3.5" to 2.5" tapered, 2 lb. density foam core
<b>Jet Pump</b>	Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque	<b>Available Options</b>	
<b>Floor Drain</b>	Included	Cover Lifter	CoverCradle®, CoverCradle II, or UpRite®
<b>Water Care System</b>	FROG® In-Line Cartridge Ready	Steps	Hot Spot Collection Step (Almond, Havana, and Storm), Polymer Step (Ash)
		Entertainment	Wireless Sound System

Actual colors and products may vary from print representation. See dealer to verify. \*Includes water and 5 adults weighing 175 lbs. each. \*\*Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. \*\*\* G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater. © 2021 Watkins Wellness - Rev. D