

HOT SPOT<sup>®</sup> COLLECTION

# STRIDE<sup>®</sup>



3

People

20

Jets

Lounge

Seating

115 or 230

Voltage

7' x 5'5" x 29"

Dimensions

FROG<sup>®</sup> In-Line Cartridge Ready

Water Care

HOT SPOT® COLLECTION

# STRIDE®



Stride spa shown with Alpine White shell and Almond cabinet.


#### Shell Colors



#### Cabinet Colors



#### Cover Colors



<b>Seating Capacity</b>	3 people	<b>Control System</b>	IQ 2020® 115 V / 20 amp,** 60 Hz (Includes G.F.C.I. protected power cord) or 115 V / 30 amp*** or 220 V / 50 amp,*** 60 Hz
<b>Dimensions</b>	7' x 5'5" x 29" / 2.13 m x 1.65 m x 0.74 m	<b>Lighting – Interior</b>	6 multi-color LED points of light, dimmable
<b>Water Capacity</b>	225 gallons / 850 liters	<b>Lighting – Exterior</b>	4 multi-color LED points of light, dimmable
<b>Weight</b>	570 lbs. / 260 kg dry; 2,975 lbs. / 1,350 kg filled*	<b>Heater</b>	No-Fault® 1,000 W / 115 V or 4,000 W / 230 V
<b>Jets</b>	20 total <ul style="list-style-type: none"> <li>• 1 XL Directional Hydromassage jet</li> <li>• 1 XL Rotary Hydromassage jet</li> <li>• 3 Directional Hydromassage jets</li> <li>• 1 Rotary Hydromassage jet</li> <li>• 14 Directional Precision® jets</li> </ul>	<b>Energy Efficiency</b>	FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
<b>Jet Pump</b>	Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque	<b>Effective Filtration Area</b>	30 sq. ft., top loading
<b>Floor Drain</b>	Included	<b>Vinyl Cover</b>	3.5" to 2.5" tapered, 1.5 lb. density foam core
<b>Water Care System</b>	FROG® In-Line Cartridge Ready	<b>Available Options</b>	
		Cover Lifter	CoverCradle®, CoverCradle II, or UpRite®
		Steps	Hot Spot Collection Step (Almond, Havana, and Storm), Polymer Step (Ash)

Actual colors and products may vary from print representation. See dealer to verify. \*Includes water and 3 adults weighing 175 lbs. each. \*\*Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. \*\*\* G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater. © 2021 Watkins Wellness - Rev. D